


EXCHANGE ARGUMENTS

EXCHANGE ARGUMENTS ^{feasible}

- take any proposed solution (s) for the given problem, then look for the first disagreement between s and the solution we produce
- make a new solution s' for s that:
 - ① fixes the disagreement without introducing earlier disagreements
 - ② doesn't reduce the quality of the solution (s' is at least as good as s)


MAXIMAL INTERVAL SELECTION

- input : a collection of intervals in time
- output : the biggest subset of non-overlapping intervals (max number of intervals)
- Alg : sort by endtime, select the interval that ends earliest, delete all overlapping intervals



HOMEWORK PROBLEM EXAMPLE

- input : collection of assignments, each with a deadline and processing times
- output : schedule of assignments that minimizes the summed lateness
- Alg : sort by deadlines process



* IF i finishes before its deadline in S :

→ k now finishes when i is finished in S , which was before its deadline, which was before k 's deadline, so k finishes before its deadline

* IF i finishes after its deadline in S :

→ Before : $\left[(\text{the time } i \text{ finished}) - d_i \right] + \left[(\text{the time } k \text{ finished}) - d_k \right]$

→ After : $\left[(\text{now time } i \text{ finishes}) - d_i \right] + \left[(\text{the time } i \text{ finished}) - d_k \right]$